



INSCREEN K-BOARD SERIES



Wall-mounting installation

Thin as wall painting with aesthetic sense of Art

Max Thickness 35mm



Full front maintenance

Module hot plug | Module swappable | Control system

Electric suction maintenance

100% front service



Pioneered 3-pieces assembly

Easy installation | Time and labor saving | Two people in two hours

※ The landing structure needs to be purchased separately. Not suit for 216" or bigger size product.

Multi-applications

Standard resolution 1920*1080P | Standard size 4 option | Conference, classroom, Training room, auditorium

Suggested meeting room

108" for 20~40, 50~80m²
135" for 30~60, 80~120m²
163" for 60~100, 120~150m²
216" for 100~200, 150~350m²

※ Support 4k resolution customized product.



Item No.	K-Board108" small size conference room	K-Board135" medium size conference room	K-Board163" medium-large size conference room	K-Board216" large size conference room
Specification				
Pixel Pitch (mm)	1.25	1.56	1.875	2.5
Resolution (dots)	1920*1080	1920*1080	1920*1080	1920*1080
Display size(mm)	2400*1350*35	3000*1687.5*35	3600*2025*35	4800*2700*35
Panel total weight (kg)	88	135	192	340
Color Depth (Bit)	14	14	14	14
Gray Scale	16384	16384	16384	16384
Refresh Rate (Hz)	2880	2880	2880	2880
Brightness (nit)	600-1000 (adjustable)	600-1000 (adjustable)	600-1000 (adjustable)	600-1000 (adjustable)
Viewing angle (H/V°)	H/160° V/160°	H/160° V/160°	H/160° V/160°	H/160° V/160°
Video interface	HDMIx3 (2 in 1 out) , USB 3.0x1 , USB 2.0x2 , RF x1			
Control interface	RJ45x1、TOUCH-USBx1、bluetooth , WIFI、 RF			
Avg. Power	655	1120	1580	2720
LED Lifetime(hrs)	≥100000	≥100000	≥100000	≥100000
Maintenance Method	Wall mounting/ground stacking and front maintenance	Wall mounting/ground stacking and front maintenance	Wall mounting/ground stacking and front maintenance	Wall mounting and front maintenance