



Product model	Specification	3m	6m/9m	12m(custom make)
 <p>MOTORS DMX</p>	Lifting height, m	3	6/9	12
	Lifting speed, m/s	0.5	0.5	0.5
	Load on cable, MAX kg	1.8	1.2	1
	Net Weight, kg	5.5	8.5	10.5
	Power consumption, W	40	40	40
	Working temperature, °C	5-45	5-45	5-45
	Protection rating	IP20	IP20	IP20
	Dimension,LxWxH, mm	252*230*125	292*292*125	324*324*125
	Packing size,LxWxH, mm	565*325*205(2in1)	365*360*365(2in1)	400*400*365(2in1)
	Gross Weight,kg	15 (2PCS in one carton)	19.6 (2PCS in one carton)	23.6 (2PCS in one carton)
	DMX channels	5/9 Channels		
	Control mode	DMX512 console or Madrix software		
	Operation menu	LCD1602 SCREEN DISPLAY		
	Power Connect	PowerCon:IN & OUT		
	DMX XLR	5PIN XLR & 3PIN XLR		
	power supply	100V-240V AC, 50-60 Hz		
	power on cable	4 cores, var. 1-24V DC 1A(max) for ch		

MAGIC SUNBALL	Specification	150	200/250	300	350
	Sphere diameter, mm	150	200/250	300	350
	Weight, kg	0.6	0.6/0.8	1.2	1.7
	Light source, RGB LEDS	42PCS TRI SMD LED	42PCS TRI SMD LED	42PCS TRI SMD LED	42PCS TRI SMD LED
	Viewing angle	360°	360°	360°	360°
	Working temperature (t), °C	-10-45	-10-45	-10-45	-10-45
	Light diffusing sphere material	white LDPE	white LDPE	white LDPE	white LDPE
	Protection rating	IP20	IP20	IP20	IP20
	Packing size,mm	690*500*525(36in1)	690*445*460(12in1)/ 835*545*565(12in1)	650*330*340(2in1)	365*360*365(1in1)
	Gross Weight,kg	30 (36PCS in one carton)	11.5/15.2(12PCS in one carton)	3 (2PCS in one carton)	2 (1PC in one carton)
RGB Tube	Specification	1000*50	1000*100		
	Height, mm	1000(Horizontal type)	1000(Vertical type)		
	diameter, mm	50	100		
	Weight, kg	0.6	1.65		
	Light source, RGB LEDS	48PCS TRI SMD LED	96PCS TRI SMD LED		
	Viewing angle	330°	360°		
	Working temperature (t), °C	-10-45	-10-45		
	Light diffusing sphere material	White LDPVC	White LDPE		
	Protection rating	IP20	IP20		
	Packing size,mm	1120*440*295(24in1)	1055*475*500(16in1)		
Gross Weight,kg	16 (24PCS in one carton)	34 (16PCS in one carton)			

