



Cabinet Size (mm)	500*500*67mm				500*750*67mm				500*1000*67mm			
Pixel Pitch (mm)	3.91	4.81	P5.9	P8.33	3.91	4.81	P5.9	P8.33	3.91	4.81	P5.9	P8.33
Pixel Density (dot/m2)	65,536	43,264	28,224	14,400	65,536	43,264	28,224	14,400	65,536	43,264	28,224	14,400
LED Sealing Type	SMD1921			SMD2727	SMD1921			SMD2727	SMD1921			SMD2727
LED Configuration	1R1G1B				1R1G1B				1R1G1B			
Module Size (mm * mm)	250*250				250*250				250*250			
Viewing Angle (H/W Deg)	160/120				160/120				160/120			
Brightness (CD/m2)	5000	5500	5500	6000	5000	5500	5500	6000	5000	5500	5500	6000
Grey Scale (bit )	14				14				14			
Refresh Rate (Hz)	1680				1680				1680			
Max./Ave. Power Consumption(W/pcs)	152/60	160/64	160/64	180/72	228/92	240/96	240/96	270/108	304/121	320/128	320/128	360/144
Cabinet Weight (Kg)	8				12				15			
Cabinet Resolution (PX* PX)	128*128	104*104	84*84	60*60	128*192	104*156	84*126	60*90	128*256	104*208	84*168	60*120
Input Voltage (V)	110V-220V(AC)											
Drive Mode:	Constant current drive											
Working Temperature (°C)	-20 ~ +60											
Working Humidity(RH)	10% ~ 85%											
Storage Temperature (°C)	-40 ~ +60											